

TOWNSHIP 28 RANGE 02 POINT IDENTIFIER # 400100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 33 & 34 only, (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William N. Gibb, Deputy Surveyor, under Contract #783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5432)

-----  
Set Cedar post 3 ft. long, 5" sq., 24" in the ground for cor. secs. 33 and 34, marked T28S S34 on NE.; and R2W S33 on NW. face, with 3 notches on E. and W. edges, from which  
A Cedar 30" dia., bears N.55°30'E., 49 lks. dist., mkd. T28S R2W S34 BT.  
A Hemlock 20" dia., bears N.1°W., 31 lks. dist., mkd. T28S R2W S33 BT.

GLO resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6238)

-----  
The cor. of secs. 33 and 34, which is a post, firmly set, marked and witnessed as described by the surveyor general. I perpetuate this cor., as follows: alongside the old cor. Set a granite stone 18x10x6 ins., 12" in the ground, for cor. of secs. 33 and 34, only, marked with 3 notches on E. and W. edges; from which  
A Cedar 30" dia., bears N.55°50'E., 49 lks. dist., mkd. T28S R2W S34 BT. (Old BT)  
A Hemlock 20" dia., bears N.1°W., 31 lks. dist., mkd. T28S R2W S33 BT. (Old BT)

Brent Knapp - For: Umpqua Indian Forest Management, LLC - 9/2021 - M179-80

-----  
Found - 18"x10"x6" stone  
Set - 5/8x30" iron rod with yellow cap marked "I.E. ENGINEERING, INC." in place of stone and placed stone alongside rod.  
Found - 37" Cedar with partially visible scribe bears N.56°E., 32.3' (record N.55°50'E., 49.0 lk.)  
New - 25" Hemlock scribed "T28S R2W S34 BT" bears N.9°E., 19.1'  
20" Hemlock scribed "T28S R2W S34 BT" bears S.76°E., 18.6'  
An aluminum post bears 3.0' North  
An aluminum post bears 5.0' East