

TOWNSHIP 28 RANGE 02 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Cor. Secs 27, 28, 33, & 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5441)

Set cedar post, 3 ft. long, 5" sq., 24" in the ground for cor. to secs. 27, 28, 33, & 34, marked T28S S 27 on NE, R2W S 34 on SE, S 33 on SW, S 28 on NW faces, with 3 notches on E & 1 notch on S edge; from which
A fir, 14" dia. bears N.77°E., 25 lks mkd: T28S R2W S27 BT
A fir, 8" dia., bears S.44°E., 9 lks. mkd: T28S R2W S34 BT
A pine, 5" dia. bears S.29°W., 7 lks. mkd: T28S R2W S33 BT
A fir, 12" dia. bears N.20°W., 11 lks mkd: T28S R2W S28 BT

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - V. Perron - July 11, 1968 - C.S. File 54/26-11

Found - Old decayed wooden post at corner point.
Orig. 14" now 20" fir, alive, N.77°E., 16.5 ft. shows good scars. We do not open.
Orig. 8" now 10" fir snag, S.44°E., 5.9 ft. shows good scars. We do not open.
Orig. 5" (?) now 22" Pine, alive S.29°W., 4.6 ft. scribe marks visible in narrow unhealed portion of upper scar. We rescribe "T28S R2W S33 CS BT"
Orig. 12" now 16" fir, alive, N.20°W., 7.3 ft., shows good scars. We do not open.
Set - Brass cap at cor. mkd: COUNTY SURVEYORS T28S R2W
OFFICE S 28 | S 27
1968 S 33 | S 34
New BT - 8" cedar S.53°E., 16.8 ft. mkd: T28S R2W CS BT.
This corner lies on moderate E slope.

10/1970 - Fd. ok - C.S. 54/40-197
Fd. BC & accessories - 9/2021 B. Knapp - M179-80