

TOWNSHIP 28 RANGE 02 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Cor. Secs. 15, 16, 21 & 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page 5445)

Set lava stone 10x12x14", 10" in the ground for cor. of secs. 15, 16, 21, & 22 mkd with 3 notches on S & E edges, from which

A chinquapin, 7" dia., bears N.21°E., 30 lks., mkd: T28S R2W S15 BT.

A fir, 60" dia. bears S.26°E., 5 lks. mkd: T28S R2W S22 BT

A fir, 48" dia. bears S.72°W., 54 lks mkd: T28S R2W S21 BT

A hemlock, 6" dia., bears N.6°W., 84 lks., mkd: T28S R2W S16 BT.

Dennis Gaylord, USFS & Deputy Co. Surveyor - Witness: Travis Northen - Sept. 16, 1977 - C.S. File 59/40-15

Found - Stone 24x20x16" set firmly in the ground marked with three grooves on the east face and three grooves on the south face.

Orig 7" now 13" Chinquapin Oak(?) snag bears N.21°E., 21.5 ft. scribing visible on partly healed blaze "T28S R2W S15 BT" (Rec N.21°E., 19.8 ft.)

Orig. 6" now 22" Hemlock bears N.6°W. 55.9 ft. has a healed blaze. (Rec. N.6°W., 55.44 ft.)

Orig. 48" now 72" D.Fir bears S.72°W., 37.1 ft. has a healed blaze. (Rec. 35.64 ft.)

Orig. 60" now 65" D.Fir snag bears S.26°E. to center of tree and S.41°E., to center of healed blaze, 3.3 ft. to center of tree. (Rec. S.26°E., 3.3 ft)

Set - Moving corner stone aside, I set in its place a 2½" brass cap on a 1" iron pipe stamped: County Surveyors Office

T28S
S 16 S 15
S 21 S 22
R2W
1977

I turned the corner stone over and placed it alongside the brass cap.

New BTs- A 11" Yew bears N.60°E., 42.2 ft. scribed "T28S R2W S15 CS BT" on a double blaze.

A 8" Chinquapin Oak bears S.64°E., 43.4 ft. scribed "T28S R2W S22 CS BT" on a double blaze.

Placed county BT signs on all bearing trees.