

TOWNSHIP 28 RANGE 02 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Cor Secs 9, 10, 15, & 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5447)

Set lava stone 10x10x12", 8" in the ground for cor. of secs. 9, 10, 15, & 16 mkd with 3 notches on E and 4 notches on S edge, from which
 A fir, 6" dia. bears N.30°E., 25 lks. mkd: T28S R2W S10 BT
 A maple, 4" dia. bears S.8°E., 39 lks mkd: T28S R2W S15 BT
 A fir, 36" dia. bears S.45°W., 54 lks mkd: T28S R2W S16 BT
 A maple, 4" dia. bears N.39°W., 25 lks mkd: T28S R2W S9 BT

Thomas E. Shrum, Jr. - For: US Plywood Corp. - July 1964 - C.S. 51/254-22

Found - 10x10x10" stone.
 Fir S.45°W., 35.6 ft.
Set - 22" D.Fir N.42°E., 120.5 ft.
 17" D.Fir N.21½°W., 150.5 ft.
 23" D.Fir S.81½°E., 154.7 ft.
 18" D.Fir S.39½°W., 135.0 ft.
Note - New BT placed & scribed. Corner located in rock pit. Upon removal of rock, permanent marker will be placed at corner.

Thomas E. Shrum, Jr. - For: US Plywood Corp. - July 1966 - C.S. 55/7

Found - 22" D.Fir N.42°E., 120.5 ft.
 17" D.Fir N.21½°W., 150.5 ft.
 18" D.Fir S.39½°W., 135.0 ft.
Set - 2½" alum. cap
This corner falls in a rock pit.

Do. Co. Surveyors Office - Randall Smith & Stephen Flaese - 11/20/95 - C.S. 64/64-8

Found - 2½" dia. alum cap on a 1" o.d. iron protrudes 12" above a 3' dia. mound of stone.
All Orig Bt's now gone
22" now 29" dia. D.Fir with a fully healed double blaze, bears N.42°E., 120.5'.
17" now 24" Dia. 2½' high solid D.Fir stump, with a fully healed blaze, bears N.21½°W., 150.5'.
23" now 24" dia. D.Fir, with a fully healed double blaze, bears S.81½°E., 154.7'.
18" now 13" dia. D.Fir, with a fully healed double blaze, bears S.39½°W., 135'.
continued next page

TOWNSHIP 28 RANGE 02 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Cor Secs 9, 10, 15, & 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Set- Alum cap on a unflanged 36" long iron pipe is driven down and stabilized with a 3½ dia. by 2' high mound of stone protrudes 7" above mound of stone. 4" dia. D.Fir double blaze and scribed "X BT", bears S.70°E., 3.3'.
Corner lies approx 60' east of a gravel road on the easterly edge of a rock quarry approx 25' higher than road.