

TOWNSHIP 28 RANGE 02 POINT IDENTIFIER # 400700

PRIMARY CORNER DESCRIPTION C C for Secs. 3 & 4 only, (North)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by William N. Gibb, Deputy Surveyor, under Contract #783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5451)

-----  
Intersect 6th standard parallel, 167 lks. W. of cor. secs. 33 & 34.

Set Cedar post 3 ft. long, 4" sq., 24" in the ground for closing cor. secs. 3 and 4, marked C C T28S R2W on S.; S3 on E.; and S4 on W. face, with 3 grooves on E. and W. faces, from which

A Yew 6" dia., bears S.76°W., 35 lks. dist. mkd. T28S R2W S4 BT.

A Hemlock 6" dia., bears S.77°E., 59 lks. dist. mkd. T28S R2W S3 BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew June 16, 1969 - C.S. File 54/40-173

-----  
Found - Orig. 6" now 10" Yew, S.76°W., 23.1 ft., alive, scribe visible on unhealed blaze.

Orig. 6" now 8" Cedar (Rec. Hemlock), East 38.9 ft. (Rec. S.77°E.) down and decayed, scribe S3 BT visible at point for closing cor.

Set 1" I.P. and brass cap marked: County Surveyors Office

T 27 S  
C. C.  
S4 | S3 R2W  
T28S

New BTs- 13" Cedar S.12°W., 10.8 ft. mkd. T28S R2W S3 CC CS BT.

28" W.Fir S.29°E., 6.4 ft. mkd. T28S R2W S3 CC CS BT.

Corner lies on steep East slope.