

TOWNSHIP 28 RANGE 02 POINT IDENTIFIER # 500241

PRIMARY CORNER DESCRIPTION West 1/4 Cor. Sec. 26 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5435)

Set yew stake, 3 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S27 on W & 26 on E face, and dig pits, 18x18x12" N & S of cor. & raised mound of earth, 3½ ft. base, 1½ ft. high, W of cor., from which

A fir, 6" dia., bears N.67°30'W., 14 lks., mkd: ¼ S27 BT.
No other tree fit to mark.

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 13 Page(s) 5494-5)

The ¼ sec. cor. established for secs. 26 & 27, which is a yew post, 12x4x4" above ground, firmly set marked ¼ S27 on W. **Hereafter this cor. will refer to sec. 27 only.** No marks are found on E face of post from which

A fir, 18" dia., bears S.41°W., 15 lks., mkd: ¼ S27 BT.
(New BT)

A fir, 10" dia., bears N.69°W., 14 lks., mkd: ¼ S27 BT.
(Old BT)

Thence N.0°10'W 0.29 chs

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for ¼ sec. cor. of 26 only,, with brass cap marked

¼S26
|
1923

from which

A fir, 14" dia., bears N.66°E., 11 lks., mkd: ¼ S26 BT.

A fir, 14" dia., bears S.75°E., 9 lks., mkd: ¼ S26 BT.