

TOWNSHIP 28 RANGE 02 POINT IDENTIFIER # 500301

PRIMARY CORNER DESCRIPTION CC Secs. 23 & 26, West

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5436)

Set fir stake, 3 ft. long, 4" sq., 24" in the ground for cor. secs. 22, 23, 26 and 27, marked T28S S23 on NE., R2W S26 on SE., S27 on SW., and S22 on NW. face, with two notches on S and E edges, and dig pits, 18x18x12", in each sec. 5½ ft., and raise mound of earth, 3½ ft. base, 1½ ft. high, W of cor., from which

A cedar, 18" dia., bears S.71°W., 24 lks., mkd: T28S R2W S27 BT.

A cedar, 10" dia., bears N.58°W., 11 lks., mkd: T28S R2W S22 BT.

No other tree fit to mark.

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 13 Page(s) 5495-6)

The cor. established for secs. 22, 23, 26 and 27, which is a basalt stone, 12x12x8" above ground, instead of a post, as shown in the field notes, firmly set, marked with 2 notches on S and E edges. **Hereafter, this cor. will refer to secs. 22 and 27 only.** I mark the cor. stone, S 27 on SW. and S 22 on NW face, from which

A cedar, 18" dia., bears S.71°W., 24 lks., mkd: T28S R2W S27 BT. Old BT

A cedar, 10" dia., bears N.58°W., 11 lks., mkd: T28S R2W S22 BT. Old BT

N.0°10'W., 0.53 chs.

Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for **cor., of secs. 23 & 26 only**, with brass cap marked

	T28S
S22	<u>S23</u>
	S26
	R2W
	1923

from which

A fir, 26" dia. bears N.32°E., 10 lks mkd: T28S R2W S23 BT

A fir, 28" dia. bears S.34°E., 63 lks mkd: T28S R2W S26 BT