

TOWNSHIP 28 RANGE 02 POINT IDENTIFIER # 500341

PRIMARY CORNER DESCRIPTION West 1/4 Cor. Sec. 23 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Pages 5436-7)

Set fir stake, 3 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S22 on W & 23 on E face; from which
A fir, 8" dia., bears S.35°W., 11 lks., mkd: ¼ S22 BT.
A fir, 10" dia., bears East, 10 lks., mkd: ¼ S23 BT

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 13 Page(s) 5496-7)

The ¼ sec. cor., established for secs. 22 and 23, which is a sound fir post, 12x4x4" above ground, marked ¼ S22 on W.; and witnessed by one bearing tree. No bearing tree is found east of line as shown in the field notes. **Hereafter this corner will refer to sec. 22 only;** from the corner

A fir, 8" dia., bears S.75°W., 10 lks., mkd: ¼ S22 BT; old bearing tree.

A fir, 14" dia., bears N.42°W., 10 lks., mkd: ¼ S22 BT; new bearing tree.

Thence, N.0°15'W. 0.70 chs.

Set an iron post, 3 ft. long, 1" dia., 27", in the ground, for ¼ sec. cor. of sec. 23 only, with brass cap marked

¼ S23
|
1923

from which

A fir, 14" dia., bears N.54°E., 12 lks., mkd: ¼ S23 BT.

A fir, 22" dia., bears S.87°E., 23 lks., mkd: ¼ S23 BT.