

TOWNSHIP 28 RANGE 02 POINT IDENTIFIER # 500441

PRIMARY CORNER DESCRIPTION West 1/4 Sec. 14 only

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Pages 5437-8)

Set cedar post, 3 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S on 15 on W & 14 on E face; from which
A fir, 10" dia., bears S.5°W., 23 lks., mkd: ¼ S15 BT.
A fir, 10" dia., bears N.85°E., 30 lks., mkd: ¼ S14 BT.

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 13 Page(s) 5498-9)

The ¼ sec. cor. established for secs. 14 & 15, which is a cedar post, 12x4x4" above ground, marked ¼ S15 on W. **hereafter this corner will refer to sec. 15 only.** No marks are found on E face of cor. post, from which
A fir, 15" dia., bears S.27°W., 23 lks., mkd: ¼ S15 BT; old BT.
A fir, 10" dia., bears N.18°W., 35 lks., mkd: ¼ S15 BT; new BT.

Find no trace of old bearing tree in Sec. 14.
Thence N.0°16'E., 1.01 chs.

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for ¼ sec. cor., of sec. 14 only, with brass cap marked

¼S14
|
1923

from which

A cedar, 8" dia., bears N.59°E., 25 lks., mkd: ¼ S14 BT.
A hemlock, 5" dia., bears S.67°E., 24 lks. mkd: ¼ S14 BT