

TOWNSHIP 28 RANGE 02 POINT IDENTIFIER # 500501

PRIMARY CORNER DESCRIPTION CC Secs. 11 & 14, West

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5438)  
-----  
Set cedar post, 3 ft. long, 4" sq., 24" in the ground for cor. to secs. 10, 11, 14, & 15, marked T28S S 11 on NE, R2W S 14 on SE, S 15 on SW, S 10 on NW faces, with 4 notches on S & 2 notches on E edge; from which  
A fir, 10" dia. bears N.70°E., 35 lks mkd: T28S R2W S11 BT  
A hemlock, 5" dia., bears S.45°E., 20 lks., mkd: T28S R2W S14 BT.  
A hemlock, 36" dia., bears S.59°W., 44 lks., mkd: T28S R2W S15 BT.  
A hemlock, 24" dia., bears N.12°W., 15 lks., mkd: T28S R2W S10 BT.

GL0 survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 13 Page(s) 5499-5500)  
-----  
The cor. established for secs. 10, 11, 14 and 15 which is a cedar post, 12x4x4" above ground, firmly set, in good condition marked T28S S10 on NW and R2W, S15 on SW face. Hereafter this corner will refer to secs. 10 & 15 only. No marks are found referring to secs. 11 & 14, and no bearing trees are found east of line as shown in the field notes; from the corner  
A hemlock, 36" dia., bears S.59°W., 15 lks., mkd: T28S R2W S15 BT; old BT.  
A hemlock, 24" dia., bears N.12°W., 44 lks., mkd: T28S R2W S10 BT; old BT.  
N.0°20'W., 0.91 chs.  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 11 & 14 only, with brass cap mkd  
S10 | T28S  
      | S11  
      | S14  
      | R2W  
      | 1923  
from which  
A fir, 40" dia., bears N.64°E., 22 lks. mkd: T28S R2W S11 BT  
A cedar, 28" dia., bears S.45°E., 60 lks., mkd: T28S R2W S14 BT.

Thomas E. Shrum, Jr. - For: US Plywood Corp. - Sept. 9, 1963  
- C.S. File 51/254-21  
-----  
Found - Brass cap cont. next pg

TOWNSHIP 28 RANGE 02 POINT IDENTIFIER # 500501

PRIMARY CORNER DESCRIPTION CC Secs. 11 & 14, West

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

42" D.Fir N.64°E., 14.5 ft. (Sec. 11) 32" Cedar, S.45°E., 39.6 ft. (Sec. 14)
Thomas E. Shrum, Jr. - For: US Plywood Corp. - July 1966 - C.S. File 55/7 ----- Found - Orig. BT: 42" D.Fir, now stump, N.64°E., 16.1 ft. Orig. scribe vis. Orig. BT: 32" Cedar, now 23" cedar stump, S.45°E., 39.9 ft., (Orig. face burnt out, rescribed) Set - Reset 2½" brass cap 28" D.fir stump N.69°W., 11.3 ft. Area around section corner logged & burnt
2