TOWNSHIP 28 RANGE 02 POINT IDENTIFIER # 500541

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 11 only, West

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5439)

Set cedar post, 3 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S10 on W & 11 on E face and dig pits, 18x18x12" N & S of cor. & raise mound of earth, 3½ ft. base, 1½ ft. high W of cor., from which

A hemlock, 6" dia., bears N.2°W., 16 lks., mkd: ¼ S11 BT.

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 13 Page(s) 5500-1)

The sec. cor., established for secs. 10 & 11, which is a cedar post, 12x4x4" above ground, firmly set, in good condition, marked ¼ S10 on W. **Hereafter this cor. will refer to. sec. 10 only.** No marks are found referring to sec. 11; from the corner

A hemlock, 6" dia., bears S.89°W., 16 lks., mkd ¼ S10 BT; old bearing tree.

A hemlock, 8" dia., bears.N.60°W., 40 lks. mkd ¼ S10 BT; new bearing tree.

Old pits and mound, not visible.

Thence N.0°12'W., 0.75 chs.

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for ¼ sec. cor. of sec. 11 only, with brass cap marked

¼S11
1923

from which

A hemlock, 10" dia., bears N.16°E., 70 lks., mkd: ¼ S11 BT

A hemlock, 8" dia., bears S.81°E., 32 lks., mkd: ¼ S11 BT

Thomas E. Shrum, Jr. - For: US Plywood Corp. - July 1966 - C.S. File 55/7

Area around ¼ corner has been logged & the orig. BTs destroyed. Before logging, I buried ¾"x36" iron rod at ¼ corner at location of 2" brass cap.

From ¾"x36" rod; Set

Orig. 2" Brass cap

72" D.Fir stump N.44°E., 69.4 ft.

48" Cedar stump N.83°E., 13.3 ft.