

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 3 only, East

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5440)

Set lava stone 10x10x12", 8" in the ground for ¼ sec. cor. mkd. ¼ on W face, and raise mound of stone, 2 ft. base, 1½ ft. high, W of cor. from which
A fir, 12" dia., bears N.38°W., 62 lks., mkd: ¼ S3 BT.
No other tree fit to mark.

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 13 Page(s) 5502)

The ¼ sec. cor., established for secs. 2 and 3, which is a lava stone, 10x8x4" above ground, firmly set, marked ¼ on W face. **Hereafter, this cor. will refer to sec. 3 only.** I mark the stone, ¼ S3 on W face, from which
A fir, 24" dia., bears S.84°W., 52 lks., marked ¼ S3 BT; new bearing tree.
A fir, 12" dia., bears N.53°W., 62 lks., marked ¼ S3 BT; old bearing tree.

Douglas Co. Surveyors Office - Larry E. Monrean, Deputy - Terrie Plouff - July 13, 1981 - C.S. File 61/27-15

Found - 10x6x6" stone sitting loose on top of ground with a very faint 4 & no other marks distinguishable (Rec. 10x10x12") The mound of stone from the 1909 orig. survey notes not found.
Orig. BT not found.
A badly decayed fir stump bears S.84°W., 34.3 ft. 1923 resurvey.
26" fir (Orig. 12") snag bears N.53°W., 40.9 ft. Tree has well healed blaze. We open a portion of blaze & find a scribed S.
Set - At position of found stone, we set a 1"x36" IP with a BC attached, marked Douglas County Surveyor T28S R2W ¼ S3 1981.
We bury found stone along west side of monument.
New BTs- 12" W.Fir blazed & scribed ¼ S3 CS BT bears S.39°W., 10.0 ft.
10" W.Fir blazed & scribed ¼ S3 CS BT bears N.81°W., 25.9 ft.
Note - The monument marking the west ¼ Cor. Sec. 2 bears North 40.8 ft.