TOWNSHIP 28 RANGE 02 POINT IDENTIFIER # 500641

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 2 only, West

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5440)

Set lava stone 10x10x12", 8" in the ground for ¼ sec. cor. mkd. ¼ on W face, and raise mound of stone, 2 ft. base, 1½ ft. high, W of cor. from which

A fir, 12" dia., bears N.38°W., 62 lks., mkd: ¼ S3 BT.
No other tree fit to mark.

GLO survey by Fred Mensch, US Cad. Engineer - Under special instructions dated June 7, 1922 - (DCSO rec Vol 13 Pg 5502)

The ¼ sec. cor., established for secs. 2 and 3, which is a lava stone, 10x8x4" above ground, firmly set, marked ¼ on W face. **Hereafter, this cor. will refer to sec. 3 only.** I mark the stone, ¼ S3 on W face, from which

A fir, 24" dia., bears S.84°W., 52 lks., marked ¼ S3 BT; new bearing tree.
A fir, 12" dia., bears N.53°W., 62 lks., marked ¼ S3 BT; old bearing tree.

N.0°3'E., 0.62 chs.

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for ¼ sec. cor. of sec. 2 only, with brass cap marked

| ¼S2
| 1923

from which

A yew, 12" dia., bears N.64°E., 15 lks., mkd: ¼ S2 BT.
A yew, 6" dia., bears S.53°E., 19 lks., mkd: ¼ S2 BT.

Douglas Co. Surveyors Office - Larry E. Monrean, Deputy - Terrie Plouff - July 13, 1981 - C.S. File 61/27-14

Found - Orig. 1923 GLO brass cap firmly set, & protruding 10" above ground marked | ¼ S2
1923

7" dia., dead fork (Orig 12") of a yew with unhealed blaze scribed ¼ S2 BT, bears N.64°E., 9.9 ft

6" Yew with unhealed, rotting blaze scribed ¼ S2 BT bears S.53°E., 11.1 ft. to tree center at base, & 12.1 ft. to tree center at top of blaze (Rec. 12.5 ft.)

New BTs- 12" W.Fir blazed & scribed ¼ S2 CS BT bears S.79°E., 38.3 ft.

10" W.Fir blazed & scribed ¼ S2 CS BT bears N.42°E., 47.6 ft.

Note - The monument marking the East ¼ corner of sec. 3 bears South 40.8 ft.