

PRIMARY CORNER DESCRIPTION A P on No. bdy. Sec. 2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by S.C. Flint, Contract #459, dated August 3, 1882
- (DCSO records Vol. 12 Page(s) 4866)

Set Cedar post 4 ft. long, 4" sq., 24" in the ground for
standard cor. to secs. 34 and 35, marked S C T27S R2W on N.;
S35 on E.; and S34 on W. faces with 4 notches on W. and 2
notches on E. edges, from which
 A Fir 18" dia., bears N.52°E., 30 lks. dist. mkd. T27S R2W
 S35 BT.
 A Fir 24" dia., bears N.12°W., 13 lks. dist. mkd. T27S R2W
 S34 BT.
 A Hemlock 20" dia., bears S.25°E., 11 lks. dist. mkd. T28S
 R2W S3 BT.

GLO Resurvey by Morris Wygant, Compassman for Zachariah
Derrick, U.S. Deputy Surveyor, Under Contract #779, dated
Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4903-04)

The standard cor. of secs. 34 and 35, which is a post, firmly
set, marked and witnessed as described by the surveyor
general, bears North 245 lks. dist. I now change this cor.
to an Angle Point as follows:
Cut out all marks and mark A P on N. face, then cut out all
BTs and remark A P BT.

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer - under
special Instructions, dated June 7, 1922 - (DCSO records Vol.
12 Page(s) 4965)

Angle point, located by record measurement from the original
BTs, no other evidence found. At exact angle point; Set a
Cedar post, 3 ft. long, 4" sq., 24" in the ground marked AP
on N. face, from which
 A Fir 24" dia., bears N.56°E., 30 lks. dist., mkd. AP BT;
 Old bearing tree.
 A Fir 28" dia., bears N.4°W., 13 lks. dist. mkd. AP BT;
 Old bearing tree.
No iron post or stone of sufficient size is available

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew
Oct. 1968 - C.S. File 54/40-92

Found - Unrecorded U.S. Plywood alum. cap mkd. A.P., set
 from original BTs, both out of ground, scribing
 visible on NW. orig. BT.
 No trace of new bearing trees.
Set 6 ft. steel fence post alongside alum. cap.
(Cont. Next Page)

TOWNSHIP 28 RANGE 02 POINT IDENTIFIER # 501700

PRIMARY CORNER DESCRIPTION A P on No. Bdy. Sec. 2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

New BTs- 6" Yew N.14°E., 18.0 ft. mkd. "A.P. CS BT."
12" W.Fir S.81°E., 53.4 ft. mkd. "A.P. CS BT."
Corner lies 120 ft. West of CC secs. 34 & 35, T27-2, in flat
logged off unit. (Rec. dist. btwn. cors., 112.3 ft.)

Survey by Ronald A. Quimby & Romano E. Ware - For: U.S.
Forest Service - May 1980 - M 79-45

Found - Alum. cap on 3/4" I.Rod (unrecorded) mkd. "USPC
Prop. Cor. T27S R2W S34 AP T28S R2W S2 RE#4287."
10" Yew N.14°E., 18.0 ft. with visible scribe.
20" Hemlock stump, bears N.77°E., 40.1 ft. with
visible scribe.
24" Fir stump, orig. BT, down, bears North 6.0 ft.
(uproot)
12" W.Fir snag, bears S.81°E., 53.4 ft. with visible
scribe.
New Bt - 8" Fir bears South 66.0 ft. scribed "AP S2 BT", with
brass washer mkd. "RLS 1654", set in BT face.
Set post and sign 3.0 ft. East of corner.