

PRIMARY CORNER DESCRIPTION C C for Secs. 34 & 35 only, T27-2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Resurvey by Morris Wygant, Compassman for Zachariah Derrick, U.S. Deputy Surveyor, Under Contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4932)

Intersect S. bdy. of Tsp. 220 lks. S.87°07'E., of old cor. of secs.34 and 35, which I have previously changed to an angle point.

At point of intersection, I Set a Fir post 3 ft. long, 4" sq., 24" in the ground for closing cor. of secs. 34 & 35, mkd. CC T27S R2W on N.; S35 on E.; and S34 on W.; with 2 grooves on E. and 4 grooves on W. face, from which

A Cedar 30" dia., bears N.45°E., 11 lks. dist. mkd. T27S R2W S35 BT.

A Fir 36" dia., bears N.78°W., 92 lks. dist. mkd. T27S R2W S34 BT.

Fd. and used in GLO resurvey by Fred Mensch, U.S. Cadastral Engineer - under special Instructions, dated June 7, 1922 - (DCSO records Vol. 12 Page(s) 4965)

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Oct. 1968 - C.S. File 54/40-91

Found - Unrecorded U.S. Plywood alum. cap mkd., set from orig. BTs, now only sawed stumps remain.

16" Hemlock stump N.45°W., 22.5 ft. mkd. S34 BT and tag mkd. 4287.

48" Cedar stump S.62°E., 25.6 ft. mkd. S2 BT and tag mkd. 4287.

Set 6 ft. steel fence post alongside alum. cap.

New BT - 9" Cedar N.41°E., 58.1 ft. mkd. "T27S R2W S35 CC CS BT"

Corner lies 120 ft. E. of A.P. of sec. 34, in clear cut unit. (Rec. dist. btwn. corners, 112.2 ft.)

Survey by Ronald A. Quimby & Romano E. Ware - For: U.S. Forest Service - May 1980 - M 79-45

Found - Unrecorded alum. cap on 3/4" Iron rod, mkd. "USPC Prop. Cor. T27S S34 S35 T28S R2W RE 4287".

16" Fir stump bears N.50°W., 22.7 ft. (unrecorded)

15" Cedar snag, bears S.76°E., 6.6 ft. (Unrecorded)

48" Cedar stump, bears S.62°E., 25.6 ft. with visible scribe.

12" Cedar bears N.41°E., 58.1 ft. with visible scribe.

(Cont. Next Page)

TOWNSHIP 28 RANGE 02 POINT IDENTIFIER # 503700

PRIMARY CORNER DESCRIPTION C C for Secs. 34 & 35 only, T27-2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Orig. 30" Cedar stump, bears N.45°E., 7.3 ft. shows bottom of face.
Orig. 36" Fir bears N.78°W., 60.7 ft., shows axe work.
New BTs- 11" Yew bears S.76°E., 207.0 ft. scribed T28S R2W S2 BT.
11" Hemlock bears N.12°W., 184.0 ft. scribed T27S R2W S34 BT.
Set post and sign 6.6 ft. North of corner. Brass washer mkd. RLS 1005 set in BT faces.

Survey by Gerald V. Nygren - Oct. 1988 - C.S. File 63/69-35

Found - Alum. cap on a 3/4" iron rod.
16" Fir stump bears N.50°W., 22.7 ft.
15" Cedar snag bears S.76°E., 6.6 ft.
48" Cedar stump bears S.62°E., 25.6 ft. visible scribing.
12" Cedar bears N.41°E., 58.1 ft. visible scribing.
30" Cedar stump bears N.45°E., 7.3 ft.
11" Yew bears S.76°E., 207.0 ft. visible scribing.
11" Hemlock snag bears N.12°W., 184.0 ft. visible scribing.
New BT - 7" Yew bears N.3°E., 39.2 ft. scribed T27S R2W S35 BT. A 1/2" brass washer was set in BT face mkd. LS 1035.

2