

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 35 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6240)

Set a basalt stone 20x8x5 ins., 15" in the ground for 1/4 cor. of sec. 35, T28S R2W only, marked 1/4 on N. face, from which
A Fir 10" dia., bears N.25°15'E., 25 lks. dist. mkd. 1/4 S35 BT.
A Pine 12" dia., bears N.36°15'W., 43 lks. dist., mkd. 1/4 S35 BT.

GLO resurvey by Fred Mensch, under Special Instructions dated June 7, 1923 - (DCSO records Vol. 13 Page(s) 5492)

(37.09 chains)
The cor. established for 1/4 sec. cor. of sec. 35, which is a basalt stone, 15x8x5 ins. set, marked, and witnessed as described. I destroy this corner.
(West)
(40.00 chains)
Set an iron post 3 ft. long, 1" dia., 27" in the ground, for 1/4 sec. cor. of sec. 35 only, with brass cap mkd. 1/4 S 35
1923
from which
A Fir 12" dia., bears N.89°E., 20 lks. dist. mkd. 1/4 S35 BT.
A Fir 12" dia., bears N.23°W., 3 lks. dist. mkd. 1/4 S35 BT.

Douglas Co. Surveyors Office - Dennis Gaylord, U.S.F.S. (Deputized by the County) - Wit: Randal Lopez - March 23, 1978 - C.S. File 59/46-47

Found - 2 1/2" brass cap on 1" I.P. stamped U.S. General Land office Survey 1/4 S35 1923. I ADD "T28S R2W" to brass cap above the 1/4 S35.
16" D.Fir bears N.23°W., 1.98 ft. Has a healed blaze.
17" D.Fir bears N.89°E., 13.8 ft. (Rec. 13.2 ft.) Has a healed blaze.
Placed County BT signs on both trees.
Did not remonument or add accessories.