

TOWNSHIP 28 RANGE 02 POINT IDENTIFIER # 540200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 & 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 13 Page(s) 5506)

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for 1/4 sec. cor., with brass cap marked

1/4 S 26
 S 35
 1923

from which

A fir, 14" dia., bears N.39°W., 30 lks., mkd: 1/4 S26 BT.
A hemlock, 10" dia., bears S.81°E., 27 lks., mkd: 1/4 S35 BT

Dennis Gaylord, USFS & Deputy Co. Surveyor - Witness: Juan Ortegon - June 16, 1978 - C.S. File 60/11-17

Found - 1923 U.S. GLO 2 1/2 brass cap on a 3/4" I. rod properly stamped. Monument has been removed from ground by logging activities and is lying at approx. corner location.

Orig. 10" now 15" Hemlock bears S.82°W., 17.82 ft.
Has a healed scar.
Orig. 14" now a 18" D.Fir bears N.39°30'W., 19.8 ft.
Has a healed scar.

Placed County BT signs on both BTs.

Using the orig. BTs for reference, I RE-SET the GLO brass cap and build a mound of stone around pipe. I ADD "T28S R2W" to brass cap. No new accessories.