

PRIMARY CORNER DESCRIPTION A P on No. Bdy. Sec. 2

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by S.C. Flint, Contract #459, dated August 3, 1882  
- (DCSO records Vol. 12 Page(s) 4866-67)

-----  
Set Yew post 3 ft. long, 3" sq., 24" in the ground for  
standard ¼ sec. cor. marked on N. face S C ¼ S., from which  
A Fir 30" dia., bears N.50°W., 19 lks. dist. mkd. S C ¼ S  
BT.  
A Fir 32" dia., bears South 9 lks. dist., mkd. S C ¼ S BT.

GLO Resurvey by Morris Wygant, Compassman for Zachariah  
Derrick, U.S. Deputy Surveyor, Under Contract #779, dated  
Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4903)

-----  
The old standard ¼ sec. cor. which is a post, firmly set,  
mkd. and witnessed as described by the surveyor general,  
bears N. 41 lks. dist. As this line is badly out of limits  
and these old standard cors. will no longer refer to the  
secs. on the North and do not refer to the secs. on the  
South, I now change this cor. to an angle point, as follows:  
Destroy all marks on cor. and mark A P on N. face, then cut  
all bearing trees and remark, A P BT.

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer - under  
special Instructions, dated June 7, 1922 - (DCSO records Vol.  
12 Page(s) 4964)

-----  
The Angle point, which is a sound Yew post, 4" sq., 12" above  
ground, mkd. ¼ S35 on N. face. The BTs are as described in  
the notes of the Flint survey, but as the tree N. of line is  
now decayed and not suitable for permanent witness, I destroy  
the marks on both the old trees; from the post  
A Hemlock 24" dia., bears N.67°E., 21 lks. dist. mkd. AP  
BT, New BT.  
A Yew 7" dia., bears N.17°W., 16 lks. dist. mkd. AP BT,  
new BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew  
Oct. 1968 - C.S. File 54/40-93

-----  
Found - Orig. 24" now 28" Hemlock, alive, N.67°E., 13.9 ft.,  
scribe visible, on unhealed blaze. Rescribe "AP  
CS BT"  
Orig. 7" now 9" Yew, dead and broken off 4 ft. above  
ground, N.17°W., 10.6 ft., scribe visible.  
Set Brass cap at cor. mkd: County Surveyors Office

T 27 S R2W A P  
T 28 S

(Cont. Next Page)

1968

TOWNSHIP 28 RANGE 02 POINT IDENTIFIER # 543700

PRIMARY CORNER DESCRIPTION A P on No. bdy. Sec. 2

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

New BT - 50" D.Fir N.1°W., 13.2 ft. mkd. "AP CS BT"  
Corner lies on steep East slope, approx. 310 ft. East of N.  
¼ cor. Sec. 2, T28-2.

Fd. OK, June 28, 1972 by V.Tracy, DCSO

Survey by Gerald V. Nygren - oct. 1988 - C.S. File 63/69-36  
-----

Found - A Brass cap on Iron pipe.  
6 ft. high, 32" Hemlock stump, bears N.67°E., 13.9  
ft. visible scribing.  
9" Yew, dead and broken off 4 ft. above ground bears  
N.17°W., 10.6 ft., visible scribing.  
54" D.Fir, 4 ft. high stump, bears N.1°W., 13.2 ft.,  
visible scribing.  
New BTs- 8" Hemlock S.20°W., 11.0 ft. scribed "AP BT"  
18" double Yew, S.70°W., 39.1 ft., scribed "AP BT"  
Set 1/2" brass washers in BT faces mkd. "LS 1035"  
Point lies approx. 300 ft. East of ¼ cor. for sec. 2, T28-2