

TOWNSHIP 28 RANGE 02 POINT IDENTIFIER # 544100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 2 only, T29-2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6240-41)

Set a basalt stone 14x12x6 ins., 9" in the ground for cor. of secs. 1 and 2 marked with 5 notches on W. and 1 notch on E. edge; from which
A Hemlock 12" dia., bears S.35°45'E., 35 lks. dist. mkd. T29S R2W S1 BT.
A Fir 14" dia., bears S.45°W., 35 lks. dist. mkd. T29S R2W S2 BT.

Found and tied in GLO resurvey by Fred Mensch, under Special Instructions dated June 7, 1922 - (DCSO records Vol. 13 Page(s) 5492)

Douglas Co. Surveyors Office - Dennis Gaylord, U.S.F.S. (Deputized by the County) - Wit: Randal Lopez - March 23, 1978 - C.S. File 59/46-65

Found - Orig. corner stone set firmly in place. No visible marks on stone, which is soft and somewhat weathered. Stone measures 15" x 12" x 6".
20" Hemlock bears S.35°45'E., 23.1 ft. Some scribing visible on partly healed blaze.
16" D.Fir bears S.55°W., 23.1 ft. (Rec. S.45°W. 23.1 ft.) Has a healed blaze.

Placed County BT signs on both trees.
Moving corner stone aside, I SET in its place, a 2½" brass cap stamped: County Surveyors Office

T 28 S
S 2 | S 1

T 29 S R 2 W
1978

I bury corner stone alongside and build a rock mound around I.P. No new accessories.