

PRIMARY CORNER DESCRIPTION Cor. Secs. 25, 26, 35, & 36

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 13 Page(s) 5504)

Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 25, 26, 35, & 36, with brass cap mkd

T28S R2W
S 26|S 25
S 35|S 36
1923

from which

- A chinquapin, 6" dia., bears N.11°E., 22 lks., mkd: T28S R2W S25 BT.
- A chinquapin, 6" dia., bears S.64°E., 20 lks., mkd: T28S R2W S36 BT.
- A chinquapin, 8" dia., bears S.20°W., 11 lks., mkd: T28S R2W S35 BT.
- A chinquapin, 6" dia., bears N.71°W., 21 lks., mkd: T28S R2W S26 BT.

Dennis Gaylord, USFS & Deputy Co. Surveyor - Witness: Juan Ortegon - June 16, 1978 - C.S. File 60/11-16

Found - 1923 U.S. GLO brass cap on a 1½" I. Rod firmly set in the ground and properly stamped. Protrudes 10" above the ground surface.

A 7" Chinquapin stump bears S.17°W., 6.8 ft. (Rec. S.20°W., 7.26 ft. Portion of healed face is visible.

A 8" (Orig. 6") Chinquapin bears N.71°W., 11.9 ft. (Rec. 13.8 ft.) Scribing visible on partly healed face, "T28S R2W S2 6 B" A5"

Chinquapin snag bears N.11°E., 14.52 ft. The partly healed face is rotted out.

No trace of SE BT.
No new monument set.

New BTs- A 9" Chinquapin bears S.31°45'E., 17.4 ft. scribed "T28S R2W S36 CS BT" on a double blaze.

A 35" D.Fir bears S.37°W., 41.2 ft. scribed "T28S R2W S35 CS BT" on a double blaze.

A 22" White Pine bears N.54°E., 30.6 ft. scribed "T28S R2W S25 CS BT" on a double blaze.

Placed County BT signs on Orig. and new bearing trees.