

TOWNSHIP 28 RANGE 02 POINT IDENTIFIER # 606700

PRIMARY CORNER DESCRIPTION Stand. Cor. for 35 & 36 only, T27-2

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by S.C. Flint, Contract #459, dated August 3, 1882  
- (DCSO records Vol. 12 Page(s) 4867)

-----  
Set Fir post 4 ft. long, 4" sq., 24" in the ground for  
standard corner for secs. 35 and 36, marked S C T27S R2W on  
N.; S36 on E.; and S35 on W. faces, with one notch on E. and  
5 notches on W. faces, from which  
A Fir 14" dia., bears N.30°E., 23 lks. dist. mkd. T27S R2W  
S36 BT.  
A Fir 36" dia., bears N.62°W., 62 lks. dist. mkd. T27S R2W  
S35 BT.  
A Fir 10" dia., bears S.35°W., 45 lks. dist. mkd. T28S R2W  
S2 BT.

Tied corner in GLO Resurvey by Morris Wygant, Compassman for  
Zachariah Derrick, U.S. Deputy Surveyor, Under Contract #779,  
dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4903)

GLO survey by Fred Mensch, Deputy Surveyor, under Special  
Instructions dated June 7, 1922 - (DCSO records Vol. 12  
Page(s) 4963)

-----  
The standard cor. of secs. 35 and 36 which is a sound Fir  
post, 4" sq., 12" above ground, properly marked. This is  
evidently not the original corner established by Flint and  
appears to have been set at the time of the Wygant resurvey  
of this line, though not shown in the notes. From the corner  
A Fir 40" dia., bears N.58°E., 55 lks. dist. Old bearing  
tree, now dead. This tree appears to have been taken  
in the Wygant resurvey and not recorded.  
A Fir 10" dia., bears N.84°E., 62 lks. dist. mkd. T27S R2W  
S36 S C BT. New BT.  
A Fir 7" dia., bears N.1°W., 67 lks. dist. mkd. T27S R2W  
S35 S C BT. New BT.  
The original bearing trees are all destroyed by fire.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew  
Oct. 1968 - C.S. File 54/40-84

-----  
Found - Orig. BT, 40" Fir snag, 40 ft. high, N.58°E., 36.3  
ft., scribe visible.  
10" now 16" Fir, alive, N.84°E., 40.9 ft., shows  
scar. Rescribe "T27S R2W S35 SC CS BT."  
7" now 22" Fir, alive, N.1°W., 44.2 ft. scribe  
visible on open blaze. Rescribe "T27S R2W S36 SC  
CS BT."  
Set Brass cap at cor. mkd:

(Cont. Next Page)

TOWNSHIP 28 RANGE 02 POINT IDENTIFIER # 606700

PRIMARY CORNER DESCRIPTION Stand. cor. Secs. 35 & 36 only, T27-2

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

County Surveyors Office

T 27 S

S 35 | S 36 R2W

T 28 S

1968

Corner lies on East side of Red Butte Lookout Road.

Fd. OK, Aug. 2, 1976 by DCSO - C.S. File 59/18