

TOWNSHIP 28 RANGE 02 POINT IDENTIFIER # 640500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 12 & 13

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 13 Page(s) 5514-5)

-----  
Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for 1/4 sec. cor., with brass cap marked

1/4  $\frac{S\ 12}{S\ 13}$   
1923

from which

- A hemlock, 16" dia., bears N.84°E., 37 lks., mkd: 1/4 S12 BT
- A hemlock, 26" dia., bears S.71°E., 69 lks., mkd: 1/4 S13 BT

Douglas Co. Surveyors Office - Karen Cheney - Gary Langlitz - Vic Cangie - Mike Tompkins - Sept. 21, 1976 - C.S. File 59/24-14

-----  
Found - 1923 GLO brass cap properly mkd., bent to the west, firmly embedded in the ground.

- A 16" now 18" Hemlock, (now a broken stump) bears N.84°E., 24.4 ft. with visible scribing.
- A 26" Hemlock, now 28", bears S.68°E., (Rec. S.71°E.) 45.5 ft. with visible scribing.
- New BT- A 11" Yewwood bears N.36°W., 153.7 ft. scribed 1/4 S12 CS BT in double blaze.