

TOWNSHIP 28 RANGE 02 POINT IDENTIFIER # 644700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 36 only, T27-2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by S.C. Flint, Contract #459, dated August 3, 1882
- (DCSO records Vol. 12 Page(s) 4867)

Set Maple post 3 ft. long, 3" sq., 24" in the ground for
standard ¼ sec. cor. marked on N. face S C ¼ S, from which
A Hemlock 24" dia., bears S.30°E., 13 lks. dist. mkd. S C
¼ S BT.
A Hemlock 14" dia., bears S.45°W., 53 lks. dist. mkd. S C
¼ S BT.

GLO Resurvey by Morris Wygant, Compassman for Zachariah
Derrick, U.S. Deputy Surveyor, Under Contract #779, dated
Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4902)

At standard ¼ sec. cor., on S. bdy. sec. 36, which is a post,
decayed; bearing trees in good condition, and mkd. as
described by the surveyor general. I reestablish as follows:
Destroy old cor. and at the exact point, Set a Vinemaple
post, 3 ft. long, 4" sq., 24" in the ground for standard ¼
sec. cor., sec. 36, marked S C ¼ S36 on N. face.

GLO resurvey by Fred Mensch , U.S. Cadastral Engineer - under
special Instructions, dated June 7, 1922 - (DCSO records Vol.
12 Page(s) 4962)

The standard ¼ sec. cor., which is a sound Fir post, 4" sq.,
12" above ground, firmly set, mkd. S C ¼ S 36 on N. face,
from which
A Fir 36" dia., bears N.5°E., 13 lks. dist. mkd. S C ¼ S36
BT; old bearing tree.
This appears to be the original bearing tree established by
Flint, shown in the old notes as S.30°E., which bearing I
conclude to be an error of the original notes. The other old
bearing tree is not found.
A Fir 24" dia., bears N.20°W., 142 lks. dist. mkd. S C ¼
S36 BT; new bearing tree.

Looked for, not found. Oct 1967, DCSO C.S. 54/40-86