

TOWNSHIP 28 RANGE 02 POINT IDENTIFIER # 700100

PRIMARY CORNER DESCRIPTION SE Cor. for Sec. 36 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Fred Mensch , U.S. Cadastral Engineer - under special Instructions, dated June 7, 1922 - (DCSO records Vol. 15 Page(s) 6156)

Set an Iron post 3 ft. long, 3" dia., 27" in the ground for SE Cor. of T28S R2W, with brass cap mkd.

| | | |
|---------|--|-----|
| T28S | | |
| R2W | | |
| S36 | | S 6 |
| T29SR1W | | |
| 1922 | | |

from which

A Fir 5" dia., bears N.73°W., 4 lks. dist. mkd. T28S R2W S36 BT.

A Cedar 18" dia., bears N.10°W., 69 lks. dist. mkd. T28S R2W S36 BT.

(This point due S. from the cor. of Tps. 28 and 29 S., R1W on the E. bdy. T28-2)

Dennis Gaylord, U.S. Forest Service (Deputized by the DCSO - Wit: Randal Lopez - March 16, 1978 - C.S. File 59/46-52

Found - 3½" brass cap on a 3" I.P. set solidly in ground, stamped in 1922.

A 10" Orig. 5" D.Fir with a healed blaze, bears N.70°W., (Rec. N.73°W.) 2.64 ft. to face and 2.9 ft. to center of tree.

A 24" orig. 18" Cedar, bears N.10°W., 45.54 ft. Has a healed scar.

Condition report only. Did not Re-monument.
Placed County BT signs on both BTs.