

PRIMARY CORNER DESCRIPTION Sec. Cor. for 30 & 31 only, T28-1

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 13 Page(s) 5368)

Set a basalt stone 15x14x6 ins., 10" in ground for cor. of secs. 25, 30, 31 and 36, marked with 1 notch on S. and 5 notches on N. edges; from which
A Pine 16" dia., bears N.64°E., 95 lks. dist. mkd. T28S R1W S30 BT.
A Pine 10" dia., bears S.50°E., 59 lks. dist. mkd. T28S R1W S31 BT.
A Pine 14" dia., bears S.54°W., 56 lks. dist. mkd. T28S R2W S36 BT.
A Pine 20" dia., bears N.70°W., 14 lks. dist. mkd. T28S R2W S25 BT.

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer - under special Instructions, dated June 7, 1922 - (DCSO records Vol. 13 Page(s) 5481)

The cor., established for 25, 30, 31 and 36, which is a basalt stone, 14x6x5 ins. above ground, firmly set, mkd. with 1 notch on S. and 5 notches on N. edge. Hereafter this cor. will refer to secs. 30 & 31 only; I mark the cor. stone S30 on NE.; and S31 on SE. face, from which
A Pine 16" dia., bears N.64°E., 95 lks. dist. mkd. T28S R1W S30 BT. Old bearing tree.
A Pine 10" dia., bears S.50°E., 59 lks. dist. mkd. T28S R1W S31 BT. Old bearing tree.
A Fir 14" dia., bears S.54°W., 56 lks. dist., I obliterate the marks on this old BT.
A Fir 20" dia., bears N.70°W., 14 lks. dist., I obliterate the marks on this old BT.
(The NW. and SW. bearing trees are found to be Firs instead of Pines as recorded in notes of original survey.)