

TOWNSHIP 28 RANGE 02 POINT IDENTIFIER # 700304

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 30 only, T28-1

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 13 Page(s) 5368-69)

Set a basalt stone 15x12x6 ins., 10" in ground for ¼ sec. cor. marked ¼ on W. face; from which
A Fir 12" dia., bears S.20°E., 45 lks. dist. mkd. ¼ S30 BT
A Fir 20" dia., bears N.55°W., 24 lks. dist. mkd. ¼ S25 BT.

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer - under special Instructions, dated June 7, 1922 - (DCSO records Vol. 13 Page(s) 5482)

The ¼ sec. cor., established for secs. 25 and 30, which is a basalt stone 12x6x5 ins. above ground, firmly set, mkd. ¼ on W. face. Hereafter, this corner will refer to sec. 30 only; I obliterate marks on W. face of cor. stone, and mark it ¼ S30 on E. face, from which
A Hemlock 18" dia., bears N.54°E., 43 lks. dist. mkd. ¼ S30 BT. New BT.
A Fir 12" dia., bears S.20°E., 45 lks. dist. mkd. ¼ S30 BT. Old BT.
A Fir 20" dia., bears N.55°W., 24 lks. dist., I obliterate the marks on this old BT.