

PRIMARY CORNER DESCRIPTION Sec. Cor. for 18 & 19 only, T28-1

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 13 Page(s) 5370)

Set a basalt stone 12x8x8 ins., 8" in ground for cor. of secs. 13, 18, 19 and 24, marked with 3 notches on S. and N. edges, from which
A Hemlock 30" dia., bears NE. 18 lks. dist., mkd. T28S R1W S18 BT.
A Fir 40" dia., bears S.55°E., 16 lks. dist. mkd. T28S R1W S19 BT.
A Fir 24" dia., bears S.75°W., 62 lks. dist. mkd. T28S R2W S24 BT.
A Fir 30" dia., bears N.60°W., 6 lks. dist. mkd. T28S R2W S13 BT.

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer - under special Instructions, dated June 7, 1922 - (DCSO records Vol. 13 Page(s) 5485)

The cor. established for 13, 18, 19, and 24, which is a basalt stone 8x8x4 ins. above ground, firmly set, mkd. with 3 notches on N. and S. edges. Hereafter, this cor. will refer to secs. 18 and 19 only. I mark the cor. stone, S18 on NE.; and S19 on SE. face, from which
A Hemlock 30" dia., bears N.45°E., 18 lks. dist. mkd. T28S R1W S18 BT. Old BT.
A Fir 40" dia., bears S.55°E., 16 lks. dist. mkd. T28S R1W S19 BT. Old BT.
A Fir 24" dia., bears S.75°W., 62 lks. dist. I obliterate the marks on this old BT.
A Fir 30" dia., bears N.60°W., 6 lks. dist. I obliterate the marks on this old bearing tree.
This corner is on summit of spur, bears NW. and SE.

Douglas Co. Surveyors Office - Gregory E. Quibell, Deputy - Debbie Stewart, crew - July 13, 1981 - C.S. File 61/27-13

Found - Orig. stone, 8x8x12 ins., partially tipped over to the North. Found 3 notches on the N. and S. edges. Did Not find any trace of S18 & S19 mkd. on the stone in 1922.
48" Fir (orig. 40") with well healed blaze, bears S.55°E., 10.6 ft.
36" Fir stump (Orig. 24") 15" tall, with possible partial blaze, bears S.75°W., 39.4 ft. (Rec. 40.9 ft.)

(Cont. Next Page)

TOWNSHIP 28 RANGE 02 POINT IDENTIFIER # 700444

PRIMARY CORNER DESCRIPTION Sec. Cor. for 18 & 19 only, T28-1

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

38" Fir (Orig. 30") snag, still solid, with well
healed blaze, bears N.60°W., 4.0 ft.
Badly decayed stump (Orig. 30" Hemlock) bears
N.42°E., 11.9 ft. (Rec. N.45°E., 12.2 ft.)
At the exact position of the orig. stone, I SET a brass cap
mkd: Douglas County Surveyors
 | S 18 T28S
 | S 19 R 1W
 1981
protruding 3" above ground. I bury orig. stone 0.4 ft. East
of brass cap, 3" in ground, with notches edges facing N. & S.
New BTs- 11" Fir bears S.4°W., 26.5 ft. scribed T28S R2W S13
 CS BT in a double blaze.
 11" Fir bears N.65°E., 17.5 ft. scribed T28S R1W S18
 CS BT in a double blaze.
All BTs tagged with DCSO BT tags.