

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 18 only, T28-1

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 13 Page(s) 5370)

Set a basalt stone 12x10x6 ins., 8" in ground for ¼ sec. cor. marked ¼ on W. face; from which
A Hemlock 24" dia., bears S.18°E., 64 lks. dist. mkd. ¼ S18 BT.
A Fir 12" dia., bears S.70°W., 49 lks. dist. mkd. ¼ S13 BT.

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer - under special Instructions, dated June 7, 1922 - (DCSO records Vol. 13 Page(s) 5487)

The ¼ sec. cor. established for secs. 13 and 18 which is a basalt stone 10x6x4 ins. above ground, firmly set mkd. ¼ on W. face. Hereafter this cor. will refer to sec. 18 only. I obliterate the marks on W. face and mark the cor. stone, ¼ S18 on E. face, from which
A Hemlock 16" dia., bears N.13°E., 57 lks. dist. mkd. ¼ S18 BT. New BT.
A Hemlock 24" dia., bears S.18°E., 64 lks. dist. mkd. ¼ S18 BT. Old BT.
A Fir 12" dia., bears S.70°W., 49 lks. dist. I obliterate the marks on this old bearing tree.

Douglas Co. Surveyors Office - Mike Tompkins and Vic Cangie, crew - Sept. 21, 1976 - C.S. File 59/24-16

Found - A 12"x9"x5" stone. (Rec. 10"x6"x4") with "¼ 18" mkd. on East face.
A 16" now 20" Hemlock bears N.13°E., 37.6 ft. alive and well. Shows healed blaze.
Other trees are gone.
Set a 1" x 30" I. Pipe with brass cap stamped:
Douglas County Surveyor
T 28 S | R 1 W
 | S 18
 | 1/4
 1976
Replaced stone on South side of brass cap.
New BT - A 5" Yewwood bears N.54°E., 10.2 ft. mkd. ¼ S18 CS BT.