

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7 & 18 only, T28-1

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 13 Page(s) 5370-71)

- 
- Set a basalt stone 15x10x6 ins., 10" in ground for cor. of secs. 7, 12, 13 and 18, mkd. with 4 notches on S. and 2 notches on N. edges; from which
- A Pine 12" dia., bears N.38°E., 37 lks. dist. mkd. T28S R1W S7 BT.
  - A Pine 12" dia., bears S.32°E., 60 lks. dist. mkd. T28S R1W S18 BT.
  - A Fir 24" dia., bears S.10°W., 65 lks. dist. mkd. T28S R2W S13 BT.
  - A Fir 24" dia., bears N.15°W., 59 lks. dist. mkd. T28S R2W S12 BT.

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer - under special Instructions, dated June 7, 1922 - (DCSO records Vol. 13 Page(s) 5487-88)

- 
- The cor., established for secs. 7, 12, 13 and 18, which is a basalt stone 10x6x5 ins. above ground, firmly set, marked with 4 notches on S. and 2 notches on N. edge. Hereafter, this cor. will refer to secs. 7 and 18 only. I mark the cor. stone, S7 on NE. and S18 on SE. face, from which
- A Pine 12" dia., bears N.38°E., 37 lks. dist. mkd. T28S R1W S7 BT. Old BT.
  - A Pine 12" dia., bears S.32°E., 60 lks. dist. mkd. T28S R1W S18 BT. Old BT.
  - A Fir 24" dia., bears S.10°W., 65 lks. dist. I obliterate the marks on this old bearing tree.
  - A Fir 24" dia., bears N.15°W., 59 lks. dist. I obliterate the marks on this old bearing tree.