

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 7 only, T28-1

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 13 Page(s) 5371)

Set a basalt stone 15x12x8 ins., 10" in ground for ¼ sec. cor. mkd. ¼ on W. face; from which

- A Hemlock 12" dia., bears N.35°E., 34 lks. dist. mkd. ¼ S7 BT.
- A Hemlock 18" dia., bears West, 20 lks. dist. mkd. ¼ S12 BT.

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer - under special Instructions, dated June 7, 1922 - (DCSO records Vol. 13 Page(s) 5489)

The ¼ sec. cor., established for secs. 7 and 12, which is a basalt stone, 12x8x5 ins. above ground, firmly set, mkd. ¼ on W. face. Hereafter this cor. will refer to sec. 7 only. I obliterate the marks on W. face and mark the cor. stone ¼ S7 on E. face, from which

- A Hemlock 12" dia., bears N.35°E., 34 lks. dist. mkd. ¼ S7 BT. Old BT.
- A Hemlock 6" dia., bears S.55°E., 31 lks. dist. mkd. ¼ S7 BT. New BT.
- A Hemlock 18" dia., bears West, 20 lks. dist. I obliterate the marks from this old bearing tree.

Douglas Co. Surveyors Office - M. Lenora Ladig; Jim Cook, crew - Aug. 3, 1976 - C.S. File 59/18-13

Found - A 15"x12"x8" basalt stone with "¼" on W. face.

- A 12" now 21" Hemlock snag, bears N.35°E., 22.4 ft. with "¼ S7 BT" in cut open blaze.
- An 18" now 27" Hemlock bears West 13.2 ft. with well healed blaze. Tree is alive.
- An unrecorded 16" Fir bears S.60°E., 19.1 ft. Tree is alive with visible scribe marks in healed blaze.

At true corner point, Set a 1" x 36" I.P. with brass cap stamped:

Douglas Co. Surveyor
T 28 S
R2W | S 7 ¼
 | R 1W

1976

Placed original stone East of cap.
Cor. lies approx. 200 ft. North of T28S R2W Sec. Cor. for 1 & 12. Also approx. 190 ft. North of white post on Rd. #274.