

PRIMARY CORNER DESCRIPTION Sec. Cor. for 6 & 7 only, T28-1

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 13 Page(s) 5371-72)

Set a basalt stone 12x10x8 ins. 8" in ground for cor. of secs. 1, 6, 7 and 12, marked with 5 notches on S. and 1 notch on N. edges; from which
A Fir 14" dia., bears N.50°E., 45 lks. dist. mkd. T28S R1W S6 BT.
A Fir 14" dia., bears S.48°E., 40 lks. dist. mkd. T28S R1W S7 BT.
A Fir 24" dia., bears S.25°W., 34 lks. dist. mkd. T28S R2W S12 BT.
A Fir 20" dia., bears N.27°W., 48 lks. dist. mkd. T28S R2W S1 BT.

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer - under special Instructions, dated June 7, 1922 - (DCSO records Vol. 13 Page(s) 5489-90)

The cor. established for secs. 1, 6, 7 and 12, which is a basalt stone, 10x8x4 ins. above ground, firmly set, marked with 5 notches on S. and 1 notch on N. edge. Hereafter, this cor. will refer to secs. 6 & 7 only, I mark the cor. stone S6 on NE. and S7 on SE. face, from which
A Fir 18" dia., bears N.52°E., 47 lks. dist. mkd. T28S R1W S6 BT. Old BT.
A Fir 14" dia., bears S.48°E., 40 lks. dist. Old BT, now dead.
A Fir 36" dia., bears S.85°E., 51 lks. dist. mkd. T28S R1W S7 BT. New BT.
A Fir 24" dia., bears S.25°W., 34 lks. dist. I obliterate the marks on this old bearing tree.
A Fir 20" dia., bears N.27°W., 48 lks. dist. I obliterate the marks on this old bearing tree.