

TOWNSHIP 28 RANGE 03E POINT IDENTIFIER # 100300

PRIMARY CORNER DESCRIPTION Cor. Secs. 19, 30; 24, & 25 T28-2E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Lincoln Wilkes, USCE, under Group No. 62, Special Instructions dated Dec. 21, 1920, surveyed Sept 1926/Aug. 1927 - (DCSO records Vol. 24 Page(s) 10380  
-----

Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 19, 24, 25, & 30, with brass cap mkd

T28S  
R2E | R3E  
S 24 | S 19  
S 25 | S 30  
1926

from which

A hemlock, 12" dia., bears N.48°E., 36 lks., mkd: T28S R3E S19 BT.

A fir, 14" dia., bears S.17°E., 28 lks., mkd: T28S R3E S30 BT.

A fir, 30" dia., bears S.33°W., 58 lks., mkd: T28S R2E S25 BT.

A fir, 16" dia., bears N.23°W., 40 lks., mkd: T28S R2E S24 BT.