

TOWNSHIP 28 RANGE 03E POINT IDENTIFIER # 100500

PRIMARY CORNER DESCRIPTION Cor. Secs. 7, 18; 12, & 13 T28-2E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Lincoln Wilkes, USCE, under Group No. 62, Special Instructions dated Dec. 21, 1920, surveyed Sept 1926/Aug. 1927 - (DCSO records Vol. 24 Page(s) 10382  
-----

Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 7, 13, 13, & 18, with brass cap mkd

T28S	
R2E	R3E
S 12	S 7
S 13	S 18
1926	

from which

- A fir, 10" dia., bears N.50°E., 54 lks., mkd: T28S R3E S7 BT.
- A fir, 16" dia., bears S.14°E., 22 lks., mkd: T28S R3E S18 BT.
- A fir, 12" dia., bears S.57°W., 43 lks., mkd: T28S R2E S13 BT.
- A pine, 22" dia., bears N.23°W., 38 lks., mkd: T28S R2E S12 BT.