

TOWNSHIP 28 RANGE 03E POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION Cor. Secs. 6, 7, 1, & 12 T28-2E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Lincoln Wilkes, USCE, under Group No. 62, Special Instructions dated Dec. 21, 1920, surveyed Sept 1926/Aug. 1927 - (DCSO records Vol. 24 Page(s) 10383-4  
-----

Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 1, 6, 7, & 12, with brass cap mkd

T28S	
R2E	R3E
S 1	S 6
S 12	S 7
1927	

from which

- A pine, 36" dia., bears N.74°E., 52 lks., mkd: T28S R3E S6 BT.
- A fir, 8" dia., bears S.50°E., 23 lks., mkd: T28S R3E S7 BT.
- A fir, 18" dia., bears S.36°W., 45 lks., mkd: T28S R2E S12 BT.
- A pine, 10" dia., bears N.52½°W., 29 lks., mkd: T28S R2E S1 BT.