

TOWNSHIP 28 RANGE 03E POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Cor. Secs. 29, 30, 31, & 32

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer,  
under special instructions dated Dec. 27, 1920, Surveyed Aug  
1928/Aug 1929 - (DCSO records Vol. 25 Page(s) 10539-40)

-----  
Set an iron post, 3 ft. long, 2" dia., 30" in the ground, for  
cor. of secs. 29, 30, 31, & 32, with brass cap mkd

T28S R3E  
S 30 | S 29  
S 31 | S 32  
1929

from which

- A pine, 30" dia., bears N.44°E., 51 lks., mkd: T28S R3E S29 BT.
- A fir, 30" dia., bears S.27°E., 41 lks., mkd: T28S R3E S32 BT.
- A fir, 36" dia., bears S.42°E., 34 lks., mkd: T28S R3E S31 BT.
- A fir, 24" dia., bears N.76°W., 29 lks., mkd: T28S R3E S30 BT.