

TOWNSHIP 28 RANGE 03E POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Cor. Secs. 7, 8, 17, & 18

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer,  
under special instructions dated Dec. 27, 1920, Surveyed Aug  
1928/Aug 1929 - (DCSO records Vol. 25 Page(s) 10548-9)

-----  
Set an iron post, 3 ft. long, 2" dia., 30" in the ground, for  
cor. of secs. 7, 8, 17, & 18, with brass cap mkd

T28S R3E  
S 7 | S 8  
S 18 | S 17  
1929

from which

- A fir, 26" dia., bears N.70°E., 40 lks., mkd: T28S R3E S8  
BT.
- A fir, 22" dia., bears S.49°E., 16 lks., mkd: T28S R3E S17  
BT.
- A pine, 24" dia., bears S.62°W., 47 lks., mkd: T28S R3E  
S18 BT.
- A pine, 16" dia., bears N.31°W., 60 lks., mkd: T28S R3E S7  
BT.