

TOWNSHIP 28 RANGE 03E POINT IDENTIFIER # 207700

PRIMARY CORNER DESCRIPTION Cor. Secs. 31 & 32, only; T27-3E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer, under special instructions dated Dec. 27, 1920, Surveyed Aug 1928/Aug 1929 - (DCSO records Vol. 25 Page(s) 10473-4)

-----  
From the standard corner of Ts. 27S Rs. 2 & 3E: East on the S bdy of sec. 31 at 66.09 chs: Old standard cor. of sec. 31 & 32 bears N 3.88 chs. Now obliterated. (See Flint 1883 survey Vol. 24 Pg. 10047) AT 80 chs:

Set an iron post, 3 ft. long, 2" dia., 18" in ground, to bed rock, and raise a mound of stone, 2 ft. base, 1 ft. high around the post, for standard cor. of secs. 31 & 32, with brass cap marked

S|C  
T27S|R3E  
S 31|S 32  
T28S R3E  
S 5  
1929

from which  
from which  
A fir, 17" dia., bears N.76°E., 72 lks., mkd: SC T27S R3E  
S32 BT.  
A fir, 12" dia., bears N.47°W., 15 lks., mkd: SC T27S R3E  
S31 BT.