

TOWNSHIP 28 RANGE 03E POINT IDENTIFIER # 300100

PRIMARY CORNER DESCRIPTION Cor Secs 31, 32; 5, & 6 T28-3E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer, under special instructions dated Dec. 27, 1920, Surveyed June/Oct. 1927 - (DCSO) records Vol. 25 Page(s) 10798 & Vol 24 pages 10469 duplicate)

Set an iron post, 3 ft. long, 2" dia., 26" in the ground, for cor. of secs. 4, 5, 32, & 33, with brass cap mkd

| | |
|------|------|
| T28S | R3E |
| S 32 | S 33 |
| S 5 | S 4 |
| T29S | |
| 1927 | |

from which

- A pine, 14" dia., bears N.11°E., 35 lks., mkd: T28S R3E S33 BT.
- A fir, 24" dia., bears S.5°E., 85 lks., mkd: T29S R3E S4 BT.
- A fir, 22" dia., bears S.3°W., 104 lks., mkd: T29S R3E S5 BT.
- A pine, 36" dia., bears N.69°W., 16 lks., mkd: T28S R3E S32 BT.