

TOWNSHIP 28 RANGE 03E POINT IDENTIFIER # 400100

PRIMARY CORNER DESCRIPTION Cor. Secs. 33, 34; 3, & 4; T29-3E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer, under special instructions dated Dec. 27, 1920, Surveyed June/Oct. 1927 - (DCSO) records Vol. 25 Page(s) 10797 & Vol 24 pages 10468 duplicate)

Set an iron post, 3 ft. long, 2" dia., 24" in the ground, against the N side of a small ledge on steep N. slope, for cor. of secs. 3, 4, 33, & 34, with brass cap mkd

T28S	R3E
S 33	S 34
S 4	S 3
T29S	
1927	

from which

- A fir, 30" dia., bears N.12°E., 166 lks., mkd: T28S R3E S34 BT.
- A fir, 20" dia., bears S.47°E., 57 lks., mkd: T29S R3E S3 BT.
- A pine, 10" dia., bears S.11°W., 22 lks., mkd: T29S R3E S4 BT.
- A fir, 10" dia., bears N.26°W., 124 lks., mkd: T28S R3E S33 BT.