

TOWNSHIP 28 RANGE 03E POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION WC Secs. 21, 22, 26, & 27

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer,  
under special instructions dated Dec. 27, 1920, Surveyed Aug  
1928/Aug 1929 - (DCSO records Vol. 25 Page(s) 10517-8)

-----  
N.0°02'W., bet. secs. 27 & 28 - at 79.75 chains:  
Set an iron post, 3 ft. long, 2" dia., 30" in the ground, for  
cor. of secs. 21, 22, 27, & 28, with brass cap mkd

W C	
T28S	R3E
<u>S 21</u>	<u>S 22</u>
S 28	S 27
1928	

from which

A fir, 18" dia., bears N.41°E., 110 lks., mkd: W C T28S  
R3E S22 BT.

A hemlock, 15" dia., bears S.25°E., 66 lks., mkd: W C T28S  
R3E S27 BT.

A fir, 26" dia., bears S.24°W., 9 lks., mkd: W C T28S R3E  
S28 BT.

A fir, 12" dia., bears N.14°W., 82 lks., mkd: W C T28S R3E  
S21 BT.

At 80.00 chains

Point for cor. of secs. 21, 22, 27 & 28, falls in the middle  
of Castle Rock Creek, 30 lks. wide, course NW