

TOWNSHIP 28 RANGE 03E POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Cor Secs 9, 10, 15, & 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer, under special instructions dated Dec. 27, 1920, Surveyed Aug 1928/Aug 1929 - (DCSO records Vol. 25 Page(s) 10522)

Set an iron post, 3 ft. long, 2" dia., 12" in the ground, to bed rock, and raise a mound of stone, 3 ft. base, 1½ ft. high, around the post, for cor. of secs. 9, 10, 15, & 16, with brass cap mkd

T28S R3E
S 9 | S 10
S 16 | S 15
1929

from which

- A fir, 14" dia., bears N.65°E., 12 lks., mkd: T28S R3E S10 BT.
- A fir, 12" dia., bears S.42°E., 23 lks., mkd: T28S R3E S15 BT.
- A fir, 24" dia., bears S.73°W., 130 lks., mkd: T28S R3E S16 BT.
- A fir, 20" dia., bears N.22°W., 84 lks., mkd: T28S R3E S9 BT.