

TOWNSHIP 28 RANGE 03E POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Cor Secs 3, 4, 9, & 10

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer, under special instructions dated Dec. 27, 1920, Surveyed Aug 1928/Aug 1929 - (DCSO records Vol. 25 Page(s) 10524)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 3, 4, 9, & 10, with brass cap mkd

T28S R3E  
S 4 | S 3  
S 9 | S10  
1929

from which

- A larch, 24" dia., bears N.16°E., 28 lks., mkd: T28S R3E S3 BT.
- A larch, 18" dia., bears S.18°E., 40 lks., mkd: T28S R3E S10 BT.
- A larch, 18" dia., bears S.52°W., 24 lks., mkd: T28S R3E S9 BT.
- A larch, 24" dia., bears N.24°W., 21 lks., mkd: T28S R3E S4 BT.