

TOWNSHIP 28 RANGE 03E POINT IDENTIFIER # 407700

PRIMARY CORNER DESCRIPTION South Cor Secs 33 & 34; T27-3E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer, under special instructions dated Dec. 27, 1920, Surveyed Aug 1928/Aug 1929 - (DCSO records Vol. 25 Page(s) 10478)

East on the S bdy of sec. 32 at 65.25 chs: Old standard cor. of secs. 32 bears N 3.25 chs. Now obliterated. (See Flint 1883 survey Vol. 24 Pg. 10048) AT 80 chs:
Set an iron post, 3 ft. long, 2" dia., 18" in ground, to bed rock, and raise a mound of stone, 2 ft. base, 1 ft. high, around the post, for standard cor. of secs. 33 & 34, with brass cap mkd

S C
T27S|R3E
S 33|S 34
T28S|R3E
S 3
1929

from which

- A fir, 5" dia., bears N.37°E., 21 lks., mkd: S C T27S R3E S34 BT.
- A fir, 6" dia., bears N.40°W., 22 lks., mkd: S C T27S R3E S33 BT.