

TOWNSHIP 28 RANGE 03E POINT IDENTIFIER # 500100

PRIMARY CORNER DESCRIPTION Cor Secs 34, 35; 2, & 3 T29-3E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer, under special instructions dated Dec. 27, 1920, Surveyed June/Oct. 1927 - (DCSO) records Vol. 25 Page(s) 10796 & Vol 24 pages 10466-7 duplicate)

Set an iron post, 3 ft. long, 2" dia., 24" in the ground, in a small mound of stone, for cor. of secs. 2, 3, 34, & 35, with brass cap mkd

T 28 S R 3 E
S 34 | S 35
S 3 | S 2
T 29 S
1927

from which

- A fir, 48" dia., bears N.66°E., 29 lks., mkd: T28S R3E S35 BT.
- A fir, 30" dia., bears S.18°E., 18 lks., mkd: T29S R3E S2 BT.
- A fir, 24" dia., bears S.55°W., 38 lks., mkd: T29S R3E S3 BT.
- A cedar, 9" dia., bears N.20°W., 16 lks., mkd: T28S R3E S34 BT.