

TOWNSHIP 28 RANGE 03E POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Cor. Secs. 14, 15, 22, & 23

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer,  
under special instructions dated Dec. 27, 1920, Surveyed Aug  
1928/Aug 1929 - (DCSO records Vol. 25 Page(s) 10508-9)

-----  
Set an iron post, 3 ft. long, 2" dia., 30" in the ground, for  
cor. of secs. 14, 15, 22, & 23, with brass cap mkd

T28S R3E  
S 15 | S 14  
S 22 | S 23  
1928

from which

- A fir, 4" dia. bears N.27½°E., 33 lks mkd: T28S R3E S14 BT
- A fir, 7" dia. bears S.63½°E., 44 lks mkd: T28S R3E S23 BT
- A fir, 5" dia. bears S.52½°W., 65 lks mkd: T28S R3E S22 BT
- A fir, 9" dia. bears N.10½°W., 63 lks mkd: T28S R3E S15 BT