

TOWNSHIP 28 RANGE 03E POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 35 & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer, under special instructions dated Dec. 27, 1920, Surveyed Aug 1928/Aug 1929 - (DCSO records Vol. 25 Page(s) 10492)

Set an iron post, 3 ft. long, 1" dia., 30" in the ground, for 1/4 sec. cor., with brass cap marked

1/4
S 35 | S 36
1928

from which
A twin fir, 36" dia., bears S.20°E., 73 lks. mkd: 1/4 S36 BT
A fir, 20" dia., bears N.42°W., 189 lks., mkd: 1/4 S35 BT.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 9/17/2021 (filed 3/21/2023) - C.S. File 67/55-51

Found - 2 1/2" dia., brass cap marked as described on a 3/4" ID iron pipe, projecting 8" above ground.
A 44" dia., 4 ft. tall sawn & bark-less twin fir stump with a fully healed blaze bears S.18°E., 48.2 ft. OBT
A 21" dia., approx. 40 ft. tall dead Fir snag with an unhealed and rotted blaze showing partial scribe marks, bears: N.42°W., 124.7 ft. as per record. OBT

New - 48" dia., W.Fir, has USFS location tag indicating the tree is N.74°E., 52 ft. from cor. We do not scribe but add side-center spike. Tree bears N.70°E., 51.6 ft.
19" dia., Noble Fir scribed "1/4 S36" "CS BT" on a double blaze, bears S.5°E., 104.0 ft.
16" dia., Noble Fir has USFS location tag indicating the tree is N.43°W., 43.8 ft. from corner. We do not scribe but add side-center spike, tree bears N.47°W., 43.8 ft.
19" dia., Noble Fir, tree is marked with a Douglas County location tag. Tree is approx. South 140 ft

Note - Monument near north end and on East edge of a meadow in a mixed Fir, old growth forest. Monument is on gentle North slope.
Compass decl. 14 1/2°E.

Coordinates: WGS 84 LAT: N 43°05'26.77" W 122°25'14.78"