

TOWNSHIP 28 RANGE 03E POINT IDENTIFIER # 700500

PRIMARY CORNER DESCRIPTION Cor. Secs. 12, 13; 7 & 18 T28-4E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer, under special instructions dated Dec. 27, 1920, Surveyed Aug 1928/Aug 1929 - (DCSO records Vol. 25 Page(s) 10488-9)

-----  
Set an iron post, 3 ft. long, 2" dia., 30" in the ground, for cor. of secs. 7, 12, 13, & 18, with brass cap mkd

T28S	
R3E	R4E
S 12	S 7
S 13	S 18
1928	

from which

- A fir, 24" dia., bears N.69½°E., 62 lks., mkd: T28S R4E S7 BT.
- A fir, 32" dia., bears S.52½°E., 75 lks., mkd: T28S R4E S18 BT.
- A fir, 6" dia., bears S.56½°W., 36 lks., mkd: T28S R3E S13 BT.
- A fir, 8" dia., bears N.54½°W., 94 lks., mkd: T28S R3E S12 BT.