TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 100140

PRIMARY CORNER DESCRIPTION 1/4 Cor. to sec. 31; & Sec. 36 T.28-4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H. Byars, Contract #376, dated Jan. 22, 1881. (DCSO records Vol. 13, Pg. 5525)

Set 1/4 section post from which:
A Fir, 12" dia. bears N.85°W., 18 lks. dist.
A Fir, 18" dia. bears N.65°E., 10 lks. dist.

Doug. County Surveyor's Office - James W Byron, Dale McFarland, Jim Powell - August 1961 C.S. File 49/67-23

Found - Orig. 18", now 24" Fir, N.65°E., 6.6' shows good scars. I do not open.
Orig. 12", now 13" Fir, N.76°W., 13.0' (rec. N.85°W., 11.9') Note - this BT is in small slide area & out of position, shows good scribing "¼S"
Set Brass Cap at Cor. Mkd: County Surveyor's Office, 1961 East ¼ S36 T28S R4W.
New BT - 20" R.Fir, bears S.57°W., 14.0' mkd: ¼ S36 CS BT.

Ken Hoffine - For: Lone Rock Management Co. - May 2016 - C.S. File 65/94-2

Found - 1961 County cap 1.5 ft above ground.
24" orig. D.Fir bears N.72½°E., 7.3 ft (record N.65°E., 6.6 ft) healed face and tag
Rotten stub original 12' BT bears N.75¼°W., 13.0 ft (record N.76°W., 13.0 ft) remnant of face.
Rotten stub bears S.56°W., 14.3 feet (record S.57°W., 14.0 ft) remnants of face and tag
New - 13" D.Fir bears N.59½°W., 20.9 ft we scribe T28S R4W ¼ S36 BT and tag tree
Corner lies on north slope. Old skid road lies 20 ft south of corner. Put U-post approx. 1.0 feet north of corner