

TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 100203

PRIMARY CORNER DESCRIPTION Corner to Secs. 25 & 36 only, T28-4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford under contract #44 dated May 30, 1854. (DCSO rec. Vol. 13 Pg. 5526)

Set post for corner from which:

- A Laurel, 12" dia. bears N.50°E., 46 lks. dist.
- A Fir, 14" dia. bears S.55°E., 5 lks. dist.
- A Fir, 34" dia. bears S.68°W., 63 lks. dist.
- A Laurel, 12" dia. bears N.65°W., 42 lks. dist.

Doug. County Surveyors Office - James W. Byron, Deputy.
Dale McFarland, Jim Powell. Aug. 1961. C.S. file no. 49/67.

Found - Orig. 12" now 18" Laurel N.65°W., 27.7'. We open and find good scribe marks.

Orig. S.W. BT. now a rotted stump.

Set - Brass Cap at corner mkd:

County Surveyor's S25 | T28S
Office 1961 R4W S36 | R3W

New BTs - 20" R.Fir bears S.71°W., 21.0' mkd: T28S R4W S36
CS BT.

10" Cedar bears N.23°W., 25.0' mkd: T28S R4W S25
CS BT.

Ken Hoffine - For: Lone Rock Management Co. - May 2016 - C.S.
File 65/94-2

Found - 1961 County cap 1.5 ft above ground
14" Cedar bears N.23³/₄°W., 24.8 ft (record N.23°W, .
25.0 ft) healed face and tag.

Low D.F. stump bears S.71°W., 20.9 feet (record
S.71°W., 21.0 feet) no visible marks, tag on
top of stump.

New - 14" cedar bears S.80°W., 18.0 ft we scribe T28S R4W
S36 BT and tag tree.

Corner lies on south facing slope. See drawing for bearing
and distance to closing corner for section 30 & 31 T28S R3W.