

TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 100577

PRIMARY CORNER DESCRIPTION Sec. cor. for 1 & 12 only, T28-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - W.H. Byars, under contract # 376 dated Jan. 22, 1881 (DCSO rec. Vol. 13 Page 5527)

Set post for cor. to secs. 1, 12, 7 and 6 from which
A Fir 14" dia., bears N.34°E., 28 lks.
A Hemlock 12" dia., bears S.10°E., 40 lks.
A Hemlock 12" dia., bears S.2°W., 57 lks.
A Hemlock 14" dia., bears N.38°W., 40 lks.

GL0 survey by William N. Gibb, under Contract #783 dated Dec. 3, 1908 (DCSO records, Vol. 13 Page 5594)

Set Fir stake, 3 ft. long, 4" sq. 24" in the ground, for corner secs. 1 and 12, marked: T 28 S S12 on SW.; and R4W S1 on NW face, with 5 notches on S. and 1 notch on N. edge. I destroy markings on bearing trees referring to secs. 6 & 7. Other bearing trees as described by Surveyor General.

Doug. County Surveyors Office - James Byron, Deputy - M. Godfrey; Clete Putnam - July 1961 - C.S. File 49/67-13

Found - Orig. 14" now 18" Hemlock snag N.38°W., 26.4 ft., shows good scribing "T28S" on old face.
No other original BTs found.
Set Brass cap at cor. mkd:

	S 1		T28S	County	Surveyor's
R4W	S12		R3W	Office,	1961

New BTs -40" R.Fir bears N.85°W., 17.0 ft. scribed T28S R4W S1 CS BT.
20" Hemlock bears S.1½°W., 31.6 ft. scribed T28S R4W S12 CS BT.

Ted Baker - For: Seneca Jones Timber Co. - May 2001 - M138-15

Found - 1961 Douglas Co. 2½" brass cap.
42" Fir snag, N.84°W., 16.2 (scar vis.)
New BTs- 10" W.Fir, N.38°W., 50.1'
26" Cedar, S.35°W., 69.1'
All new BTs are scribed & painted red, distances to BTs are center measure.